


LAMP PHOTOMETRIC REPORT

MODEL: 92FLCOM3040/BL		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2621.6 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2863	2891	2926	2958	2967	2949	2879	2855	0- 10	301.7	301.7	11.5
20	1980	2040	2059	2064	2047	1987	1930	1935	10- 20	686.4	988.2	37.7
30	1197	1223	1240	1251	1216	1184	1172	1178	20- 30	711.6	1700	64.8
40	611.0	665.0	708.6	702.1	671.5	619.0	589.0	585.3	30- 40	608.4	2308	88
50	96.76	98.97	106.4	105.3	101.3	105.6	105.4	98.39	40- 50	223.7	2532	96.6
60	33.28	31.38	34.88	41.66	42.65	45.53	47.26	36.91	50- 60	57.92	2590	98.8
70	11.52	11.71	11.72	12.44	15.38	17.21	12.52	10.99	60- 70	24.22	2614	99.7
80	1.250	1.293	1.214	1.244	1.056	0.9557	0.9977	1.094	70- 80	7.204	2621	100
90	0.1571	0.1630	0.1634	0.1460	0.1842	0.1793	0.1879	0.1951	80- 90	0.4024	2622	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:24 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```