

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	5246.8 cd per klm.
(Luminaire orientation as tested.)	-2.0 degrees vertical
	1.5 degrees horizontal

Beam Spread	At 10% of Imax	62.6V x 62.7H
	At 50% of Imax	33.6V x 34.1H
	At 90% of Imax	12.8V x 13.8H

Beam Flux	Total	2042.2 lumens per klm.
	To 10% of Imax	1849.0 lumens per klm.
	To 50% of Imax	1004.2 lumens per klm.
	To 90% of Imax	193.5 lumens per klm.

Upward LOR	0.0 %
Downward LOR	204.2 %


Luminaire Efficiency (Light Output Ratio)	203.7 %
---	---------

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 10 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 93M20TL0530/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	93M20TL0530/BL	Imax (cd)	787.0
NOMINAL POWER (W)	5	AVAILABILITY (%)	184.6
RATED VOLTAGE (V)	48	Avai. FLUX (lm)	277.0
NOMINAL FLUX (lm)	150	LOR (%)	203.7
LAMPS INSIDE	1	TOTAL FLUX (lm)	305.6
TEST VOLTAGE (V)	48	θ @50% (H,V)	34,34DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.00
40	0.00	0.00	0.00	0.00	0.00	0.01	0.08	0.18	0.27	0.26	0.18	0.07	0.01	0.00	0.00	0.00	0.00	0.00	1.07	0.00
30	0.00	0.00	0.00	0.00	0.01	0.13	0.41	0.89	1.34	1.32	0.89	0.40	0.11	0.01	0.00	0.00	0.00	0.00	5.50	0.22
20	0.00	0.00	0.00	0.00	0.05	0.36	1.29	3.03	4.66	4.75	3.17	1.36	0.34	0.05	0.00	0.00	0.00	0.00	19.1	15.0
10	0.00	0.00	0.00	0.00	0.12	0.74	2.86	7.08	11.5	11.9	7.68	3.11	0.76	0.11	0.00	0.00	0.00	0.00	45.8	43.2
0	0.00	0.00	0.00	0.01	0.16	1.07	4.35	11.4	18.9	19.8	12.6	4.88	1.17	0.15	0.01	0.00	0.00	0.00	74.5	72.3
-10	0.00	0.00	0.00	0.01	0.15	1.07	4.51	12.2	20.7	21.6	13.4	5.07	1.20	0.14	0.01	0.00	0.00	0.00	80.0	77.9
-20	0.00	0.00	0.00	0.00	0.10	0.73	3.07	7.99	13.6	14.1	8.71	3.36	0.75	0.09	0.00	0.00	0.00	0.00	52.5	50.1
-30	0.00	0.00	0.00	0.00	0.04	0.31	1.32	3.32	5.39	5.56	3.56	1.40	0.29	0.03	0.00	0.00	0.00	0.00	21.2	17.7
-40	0.00	0.00	0.00	0.00	0.01	0.08	0.31	0.82	1.34	1.37	0.84	0.31	0.07	0.01	0.00	0.00	0.00	0.00	5.16	0.57
-50	0.00	0.00	0.00	0.00	0.00	0.01	0.04	0.11	0.16	0.14	0.08	0.04	0.01	0.00	0.00	0.00	0.00	0.00	0.57	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.00	0.00	0.00	0.02	0.65	4.52	18.2	47.1	77.9	80.8	51.1	20.0	4.70	0.59	0.02	0.00	0.00	0.00	306	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.23	14.3	44.0	75.2	78.1	48.3	16.4	0.54	0.00	0.00	0.00	0.00	0.00	---	277

one-half-peak spread: U:15.6,D:18.3 , L:19.0,R:15.3


NEMA Beam Type: Type 4

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:10 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 93M20TL0530/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 10 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


NAME: 93M20TL0530/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 10 November 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 10 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

AAI Figure

NAME: 93M20TL0530/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 10 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93M20TL0530/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-75	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-65	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.01	0.02	0.04	0.03	0.02
-55	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.03	0.08	0.10	0.12	0.16	0.16	0.14
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.04	0.07	0.12	0.20	0.34	0.61	0.83	0.96	0.99
-45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.12	0.18	0.43	1.02	2.01	3.13	3.98	4.37	4.24
-40	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.11	0.26	0.85	2.08	3.92	6.19	8.92	12.0	13.7	13.7
-35	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.03	0.09	0.19	0.96	2.70	5.51	9.58	15.8	24.7	34.6	41.0	43.9
-30	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.05	0.15	0.59	2.64	6.08	11.7	22.3	38.8	58.0	76.9	90.0	98.2
-25	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.09	0.26	1.40	5.08	11.0	23.2	44.8	75.6	109	144	172	186
-20	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.12	0.47	2.86	7.93	17.9	39.6	74.7	122	181	244	299	324
-15	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.13	0.87	4.28	10.9	26.0	57.2	108	179	270	371	458	499
-10	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.12	1.23	5.48	14.1	34.0	72.9	135	232	359	496	611	670
-5	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.10	1.47	6.24	16.0	38.9	83.7	162	271	419	581	709	773
0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.07	1.57	6.55	16.6	40.7	87.2	168	280	431	591	714	772
5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.08	1.50	6.40	16.2	39.3	85.0	151	256	394	535	643	692
10	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.08	1.26	5.77	14.6	34.6	72.3	130	212	320	436	525	563
15	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.07	0.87	4.79	11.9	27.1	56.0	101	163	239	319	382	412
20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.05	0.41	3.48	9.23	19.5	39.1	70.7	111	160	211	251	267
25	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.17	1.88	6.47	13.2	25.5	44.1	70.6	99.6	128	153	158
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.71	3.82	8.47	15.4	25.6	39.3	56.1	72.9	83.0	89.4
35	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.17	1.53	4.77	8.61	13.6	20.2	28.1	36.2	41.6	42.6
40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.06	0.30	1.63	4.12	6.99	10.1	13.3	16.8	18.8	19.1
45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.19	0.92	2.33	4.21	5.88	7.37	8.28	8.43
50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.08	0.23	0.58	1.25	1.90	2.30	2.42
55	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.06	0.07	0.07	0.08	0.11
60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.01
65	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
75	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:10 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93M20TL0530/BL	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F30 x 145	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: cilinder	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-75	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-65	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-60	0.03	0.04	0.02	0.01	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-55	0.15	0.14	0.11	0.11	0.09	0.03	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-50	0.79	0.60	0.41	0.28	0.22	0.14	0.08	0.04	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-45	3.59	2.88	2.09	1.51	0.88	0.51	0.23	0.13	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-40	12.3	10.2	7.32	5.34	3.60	2.04	0.82	0.28	0.11	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-35	42.1	35.5	24.9	15.8	9.46	5.12	2.52	0.85	0.19	0.08	0.03	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-30	94.3	82.7	62.5	41.5	23.6	11.4	5.18	2.15	0.49	0.14	0.04	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-25	178	154	117	80.3	47.3	23.2	9.37	4.03	1.15	0.23	0.07	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-20	309	259	195	131	79.9	41.2	16.3	6.43	2.19	0.39	0.10	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
-15	475	397	295	195	118	62.4	26.0	9.29	3.39	0.73	0.12	0.02	0.00	0.00	0.00	0.00	0.00	0.00	
-10	637	534	394	259	153	82.3	37.3	13.1	4.57	1.08	0.14	0.03	0.01	0.00	0.00	0.00	0.00	0.00	
-5	743	627	463	303	180	96.1	44.2	15.7	5.51	1.38	0.17	0.04	0.01	0.00	0.00	0.00	0.00	0.00	
0	751	643	477	313	184	98.2	45.6	16.8	6.04	1.57	0.18	0.05	0.02	0.00	0.00	0.00	0.00	0.00	
5	672	577	435	289	172	91.5	42.8	16.2	5.97	1.49	0.16	0.04	0.01	0.00	0.00	0.00	0.00	0.00	
10	546	469	353	238	144	77.7	36.4	14.3	5.45	1.26	0.13	0.02	0.01	0.00	0.00	0.00	0.00	0.00	
15	398	341	260	179	108	59.1	27.5	11.1	4.39	0.91	0.11	0.01	0.00	0.00	0.00	0.00	0.00	0.00	
20	259	222	171	119	75.3	40.3	18.7	8.31	3.09	0.50	0.09	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
25	156	132	104	74.1	46.3	25.2	12.0	5.58	1.67	0.21	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
30	82.6	73.1	57.3	40.8	25.7	14.3	7.30	3.13	0.64	0.08	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
35	40.7	35.4	27.9	20.0	13.0	7.59	3.74	1.20	0.16	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
40	18.4	16.2	12.8	9.66	6.35	3.42	1.22	0.23	0.06	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
45	8.07	7.13	5.70	3.91	2.02	0.67	0.15	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
50	2.38	1.97	1.29	0.60	0.21	0.07	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
55	0.09	0.08	0.08	0.06	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
60	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
65	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
75	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:10 November 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: