


LAMP PHOTOMETRIC REPORT

MODEL: 95Livial60/BL		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 714.50 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	355.4	355.5	354.2	354.2	355.8	355.4	354.9	356.3	0- 10	34.27	34.27	4.8
20	330.2	331.5	328.5	326.9	328.7	329.0	329.0	329.9	10- 20	97.05	131.3	18.4
30	289.0	290.5	287.3	285.4	285.1	284.3	283.4	286.3	20- 30	142.5	273.8	38.3
40	229.3	232.5	230.1	226.7	223.2	221.3	221.7	225.6	30- 40	161.3	435.0	60.9
50	147.0	148.8	151.7	147.2	143.7	142.0	143.0	146.7	40- 50	144.7	579.8	81.1
60	62.76	64.48	66.43	64.09	62.22	62.99	63.94	64.46	50- 60	91.66	671.4	94
70	15.08	15.76	17.55	15.88	15.28	16.07	17.27	16.71	60- 70	36.68	708.1	99.1
80	0.3382	0.3051	0.3843	0.3027	0.3178	0.4027	0.5703	0.5744	70- 80	6.183	714.3	100
90	0.1320	0.1302	0.1336	0.1353	0.1078	0.1126	0.1145	0.1066	80- 90	0.2135	714.5	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:19 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

