

ELMARK[®]

The Brand of Electricity

WALL LAMP GRF LED



GENERAL INFORMATION »

- ∴ Input voltage: 230V 50/60Hz
- ∴ Material: UV resistant ABS+ PC
- ∴ Mounting: Surface
- ∴ High voltage PCB
- ∴ Light efficiency: 18lm/W
- ∴ LED Chip: 2835 SMD
- ∴ Protection against dust and moisture: IP65

FEATURES »

- ∴ Environmentally friendly - no mercury and lead
- ∴ UV-rays stabilized, rust and corrosion-free.

AREAS OF APPLICATION »

- ∴ Suitable for outdoor use
- ∴ Additional, aesthetic, spectacular, architectural lighting of buildings, hotels, yards, garages and other outdoor spaces.

PRODUCT DETAILS »

Catalogue number	Description	Colour	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)
96GRFLED300/6BL	GRF300 LED FACADE FIXTURE	Black	6	330	4000
96GRFLED301/6BL	GRF301 LED FACADE FIXTURE	Black	6	120	4000
96GRFLED302/6BL	GRF302 LED FACADE FIXTURE	Black	6	110	4000
96GRFLED300/6GR	GRF300 LED FACADE FIXTURE	Grey	6	330	4000
96GRFLED301/6GR	GRF301 LED FACADE FIXTURE	Grey	6	120	4000
96GRFLED302/6GR	GRF302 LED FACADE FIXTURE	Grey	6	110	4000

DIMENSIONS:

Catalogue number	Length (mm)	Height (mm)	Width (mm)
96GRFLED300/6BL	255	90	42
96GRFLED301/6BL	255	90	42
96GRFLED302/6BL	255	90	42
96GRFLED300/6GR	255	90	42
96GRFLED301/6GR	255	90	42
96GRFLED302/6GR	255	90	42

ADDITIONAL INFORMATION »

Catalogue number	Barcode	Packing/Box (pcs)
96GRFLED300/6BL	3800131241627	1/20
96GRFLED301/6BL	3800131241641	1/20
96GRFLED302/6BL	3800131241665	1/20
96GRFLED300/6GR	3800131241634	1/20
96GRFLED301/6GR	3800131241658	1/20
96GRFLED302/6GR	3800131241672	1/20

