


LAMP PHOTOMETRIC REPORT

MODEL: 99POML40/WH		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1148.5 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	431.5	431.8	432.0	431.8	431.5	430.8	430.6	430.9	0- 10	41.67	41.67	3.63
20	402.1	402.5	402.8	402.3	401.6	400.3	400.2	401.1	10- 20	118.1	159.7	13.9
30	356.2	357.3	357.5	356.9	355.7	353.7	353.4	354.4	20- 30	175.1	334.9	29.2
40	299.3	300.6	300.2	300.6	298.5	295.2	295.1	296.5	30- 40	205.1	540.0	47
50	235.1	240.1	234.9	244.6	234.5	230.9	229.6	232.2	40- 50	206.5	746.5	65
60	172.7	169.3	166.4	175.3	172.3	164.1	162.0	165.7	50- 60	181.0	927.5	80.8
70	101.8	101.6	99.15	101.3	99.92	97.46	95.56	99.53	60- 70	131.9	1059	92.2
80	39.57	43.34	39.35	41.81	37.60	35.13	35.23	37.84	70- 80	72.55	1132	98.6
90	1.533	1.035	9.331	1.184	1.517	0.6589	0.6235	0.6738	80- 90	16.54	1148	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 28 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```